

Product information sheet



Supplier's name or trade mark:		Paulmann Licht GmbH	
Supplier's address		Quezinger Feld 2, DE-31832 Springe-Völksen	
Model identifier:		28650	
Type of light source:		LED	
Lighting technology used:		LED	Non-directional or directional:
Light source cap-type (or other electric interface)		E14	NDLS
Mains or non-mains:		MLS	Connected light source (CLS):
Colour-tuneable light source:		no	no
High luminance light source:		no	Envelope:
Anti-glare shield:		no	no cover
Dimmable:		nein	
Product parameters			
Parameter		Value	Parameter
Value		Parameter	
General product parameters:			
Energy consumption in on-mode (kWh/1 000 h), rounded up to the nearest integer		7	Energy efficiency class:
E		Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set:	
Useful luminous flux (Φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		806 at 360 °	2700
On-mode power (Pon), expressed in W		6,5	Standby power (Psb), expressed in W and rounded to the second decimal
Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal		Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	80	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	45	
	Depth	45	
Claim of equivalent power		yes	If yes, equivalent power (W)
60 W		Chromaticity coordinates (x and y)	
0,463		0,409	
Parameters for directional light sources:			
Peak luminous intensity (cd)		Beam angle in degrees, or the range of beam angles that can be set	
Parameters for LED and OLED light sources:			
R9 colour rendering index value		3	Survival factor
100		The lumen maintenance factor	
75			
Parameters for LED and OLED mains light sources:			
Displacement factor (cos ϕ1)		0,5	Colour consistency in McAdam ellipses
SDCM 6		Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	
no		If yes, then replacement claim (W)	
Flicker metric (Pst LM)		0	Stroboscopic effect metric (SVM)
0		0	