


# Product information sheet



<b>Supplier's name or trade mark:</b>		Paulmann Licht GmbH		
<b>Supplier's address</b>		Quezinger Feld 2, DE-31832 Springe-Völksen		
<b>Model identifier:</b>		29235		
<b>Type of light source:</b>		LED		
<b>Lighting technology used:</b>	LED	<b>Non-directional or directional:</b>	DLS	
<b>Light source cap-type (or other electric interface)</b>	GU10			
<b>Mains or non-mains:</b>	MLS	<b>Connected light source (CLS):</b>	no	
<b>Colour-tuneable light source:</b>	no	<b>Envelope:</b>	no cover	
<b>High luminance light source:</b>	no			
<b>Anti-glare shield:</b>	no	<b>Dimmable:</b>	nein	
Product parameters				
<b>Parameter</b>	Value	<b>Parameter</b>	Value	
<b>General product parameters:</b>				
<b>Energy consumption in on-mode (kWh/1 000 h), rounded up to the nearest integer</b>	5	<b>Energy efficiency class:</b>	E	
<b>Useful luminous flux (<math>\Phi_{use}</math>), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)</b>	460 at 90 °	<b>Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set:</b>	2700	
<b>On-mode power (Pon), expressed in W</b>	4,9	<b>Standby power (Psb), expressed in W and rounded to the second decimal</b>		
<b>Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal</b>		<b>Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set</b>	80	
<b>Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)</b>	<b>Height</b>	54	<b>Spectral power distribution in the range 250 nm to 800 nm, at full-load</b>	
	<b>Width</b>	51		
	<b>Depth</b>	51		
<b>Claim of equivalent power</b>	yes	<b>If yes, equivalent power (W)</b>	40 W	
	<b>Chromaticity coordinates (x and y)</b>	0,462		
		0,41		
<b>Parameters for directional light sources:</b>				
<b>Peak luminous intensity (cd)</b>	850	<b>Beam angle in degrees, or the range of beam angles that can be set</b>	38	
<b>Parameters for LED and OLED light sources:</b>				
<b>R9 colour rendering index value</b>	6	<b>Survival factor</b>	91	
<b>The lumen maintenance factor</b>	94			
<b>Parameters for LED and OLED mains light sources:</b>				
<b>Displacement factor (cos <math>\phi_1</math>)</b>	0,77	<b>Colour consistency in McAdam ellipses</b>	SDCM 6	
<b>Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.</b>	no	<b>If yes, then replacement claim (W)</b>		
<b>Flicker metric (Pst LM)</b>	0,1	<b>Stroboscopic effect metric (SVM)</b>	0	