## Product information sheet



				Paulmann					
Supplier's name or trade mark:			Paulmann Licht GmbH						
Supplier's address Model identifier: Type of light source:			Quezinger Feld 2, DE-31832 Springe-Völksen   40042   other than listed						
					Lighting technology used:		other than listed	Non-directional or directional:	NDLS
					Light source cap-type (or other electric interface)		E27		
Mains or non-mains:		MLS	Connected light source (CLS):	no					
Colour-tuneable light source:		no	Envelope:	no cover					
High luminance light source:		no							
Anti-glare shield:		no	Dimmable:	mit bestimmten Dimmern					
Product parameters									
Parameter		Value	Parameter	Value					
		Genera	l product parameters:	-					
Energy consumption in on-mode (kWh/1 000 h), rounded up to the nearest integer		40	Energy efficiency class:	G					
Useful luminous flux (Φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		65 at 360 °	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set:						
On-mode power (Pon), expressed in W		40	Standby power (Psb), expressed in W and rounded to the second decimal						
Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal			Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set						
Outer dimensions without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Height	95	Spectral power distribution in the range 250 nm to 800 nm, at full-load						
	Width	55							
	Depth	55							
Claim of equivalent power		no	If yes, equivalent power (W)						
		Chromaticity coordinates (x and y)							
		Parameters f	or directional light sources:						
Peak luminous intensity (cd)		Beam angle in degrees, or the range of beam angles that can be set							
		Parameters for	LED and OLED light sources:						
R9 colour rendering index value		Survival factor							
The lumen maintenance factor									
		Parameters for LE	D and OLED mains light sources:						
Displacement factor (cos φ1)			Colour consistency in McAdam ellipses						
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a p articular wattage.		no	If yes, then replacement claim (W)						
Flicker metric (Pst LM)			Stroboscopic effect metric (SVM)						