

Product information sheet



Supplier's name or trade mark:		Paulmann Licht GmbH		
Supplier's address		Quezinger Feld 2, DE-31832 Springe-Völksen		
Model identifier:		93084		
Type of light source:		Andere als aufgezählt		
Lighting technology used:		Andere als aufgezählt	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)		Coin		
Mains or non-mains:		MLS	Connected light source (CLS):	no
Colour-tuneable light source:		no	Envelope:	no cover
High luminance light source:		no		
Anti-glare shield:		no	Dimmable:	nein
Product parameters				
Parameter		Value	Parameter	Value
General product parameters:				
Energy consumption in on-mode (kWh/1 000 h), rounded up to the nearest integer		5	Energy efficiency class:	F
Useful luminous flux (Φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		at 90 °	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set:	2.700
On-mode power (Pon), expressed in W		4	Standby power (Psb), expressed in W and rounded to the second decimal	
Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal			Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	30	Spectral power distribution in the range 250 nm to 800 nm, at full-load	
	Width	66		
	Depth	66		
Claim of equivalent power		yes	If yes, equivalent power (W)	29 W
		Chromaticity coordinates (x and y)	0,463	
			0,42	
Parameters for directional light sources:				
Peak luminous intensity (cd)		580	Beam angle in degrees, or the range of beam angles that can be set	
Parameters for LED and OLED light sources:				
R9 colour rendering index value		3	Survival factor	100
The lumen maintenance factor		85		
Parameters for LED and OLED mains light sources:				
Displacement factor (cos ϕ1)		0,49	Colour consistency in McAdam ellipses	SDCM 3
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		yes	If yes, then replacement claim (W)	29
Flicker metric (Pst LM)		0,01	Stroboscopic effect metric (SVM)	0,01